

CATEGORY		eBoard 65 EE	eBoard 75 EE	eBoard 86 EE
DISPLAY PANEL	INCH	65 inch	75 inch	86 inch
	RESOLUTION	3840 x 2160 (4K x 2K)		
	BRIGHTNESS	350 cd / m ²	330 cd / m ²	
	CONTRAST RATIO	1200:1 (Typ.)		
	VIEWING ANGLE	178° / 178°		
	PANEL RESPONSE TIME	8ms(Typ. GTG)		
	ASPECT RATIO	16:9		
	REFRESH FREQUENCY	60hz		
	BEZEL COLOR / TYPE	Grey, Silver, Black / Aluminium & Metal Frame Round		
	PANEL	Min 30,000 hour		
INPUT / OUTPUT	HDMI Input	3 PORTS - Side		
	HDMI Output	1 PORT (Side, 4k@60Hz or 2k@60Hz)		
	VGA(DSUB) Input	1 PORT		
	AV INPUT	1 PORT		
	USB TOUCH	2 PORTS		
	USB v3.0	3 PORTS (2 FRONT ; 1 SIDE / Type-A)		
	USB v2.0	3 (2 FRONT / 1 SIDE)		
	USB C	-		
	RS232C (9600 bps)	1 (Bottom / DE-9F)		
	AUDIO	Stereo PC Audio IN / Earphone OUT / Coaxial Digital Audio OUT		
	SPEAKER	12W X 2		
NETWORK	1 Port GIGABIT ETHERNET & Wi-Fi Module (802.11a/b/g/n/ac)			
WIRELESS DISPLAY	SCREEN SHARE PRO	Stream pictures, videos, music, and documents from mobile device to eBoard / Share Content / Remote Control / Stream eBoard Disply to Mobile Device / Support IOS, Android, and DLNA Clinet		
ANDROID PLATFORM	CPU	ARM Cortex A73 Dual Core + Cortex A53 Dual Core		
	GPU	Mali G51		
	MEMORY	3G RAM / 16G FLASH		
	OPERATING SYSTEM	Android 8.0		
INTERACTIVITY	TYPE	IR sensor		
	INTERPOLATION RESOLUTION	32767 x 32767		
	TOUCH ACCURACY	>= Ø3mm		
	GLASS	Level 7 of Mohs Standard - 4T Tempered glass		
	TOUCH POINT	20 Points Touch (Basic 20 Touch / 10 Writing)		
DETECTION METHOD	Finger, brush-pencil, special pen or any opaque object			
POWER	POWER(AC)	100V ~ 240V		
	POWER CONSUMPTION	250W	400W	500W
	/ STAND BY	StandBy UNDER 0.5W		
	ENERGY RATE	8 STARS		
MECHANICAL	DIMENSION (mm)	1489 x 897 x 86	1710 x 1020 x 86	1957.2 x 1160 x 86
	PACKAGES ET BOX (mm)	1656 x 1050 x 204	1860 x 1170 x 280	2211 x 1370 x 280
	VESA® Hole Pitch (mm)	400 x 600, M8 Screw	600 x 800, M8 Screw	600 x 800, M8 Screw
	NET WEIGHT	46kg	52kg	75kg
	GROSS WEIGHT	52kg	71kg	102kg
ENVIRONMENTAL	OPERATION TEMPERATURE	0 ~ 40°C		
	STORAGE TEMPERATURE	-20 ~ 60°C		
	OPERATION HUMIDITY	20 ~ 80% RH (No Condensation)		
	STORAGE HUMIDITY	10 ~ 90% RH		
	OSD (LANGUAGE)	Multi Languages		
ACCESSORIES		Power / D-Sub / HDMI cable, User's Guide, Remote control etc		
OPTIONS		Wall Mount Bracket / Electronic motorised mobile stand / MT21 or Mt 43 PC module		



Learn more at www.a1-sys.com

For additional questions contact info@a1-sys.com, 1300 100 401

